RECEIVED
CENTRAL FAX CENTER
DEC 0 1 2006

IN THE CLAIMS:

WHAT IS CLAIMED IS:

1. (Currently Amended) A compression treatment system comprising:

a first bladder supported about ~~a~~ limb;

a second bladder supported about the limb, the bladders being in fluid communication with a fluid source and the bladders being inflated such that the first bladder is inflated for a first time period and the second bladder is inflated for a second time period, the second time period and additional time periods being initiated within the first time period; and

a pneumatic control circuit located at a controller housed separately from the inflatable bladders, the pneumatic control circuit including the controller, a single pressure sensor, a single check valve, the fluid source and a plural of solenoid valves, the ~~a~~ single pressure sensor located between the fluid source and solenoid valves and communicating with the first bladder and the second bladder, and ~~a~~ the single check valve operably connected to the fluid source and located between the fluid source and solenoid valves, wherein the single check valve prevents ~~for preventing fluid~~ leakage out of the first bladder ~~back through a pump~~, and the single pressure sensor ~~for~~

~~monitoring~~ measures bladder pressure in cooperation with the controller to calculate ~~during~~ venous refill time at the first bladder ~~detection~~.

2. (Currently Amended) A compression treatment system as recited in claim 1, further comprising ~~a~~ the controller that communicates with the pressurized fluid source and the pressure sensor ~~transducer~~, the controller being configured to monitor and regulate pressure in the bladders.

3. (Original) A compression treatment system as recited in claim 1, wherein the controller is disposed with ~~a~~ the housing that is portable.

4. (Original) A compression treatment system as recited in claim 1, wherein the housing includes a plurality of ports connectable to a plurality of bladders.

5. (Currently Amended) A compression treatment system as recited in claim 4, wherein the single pressure ~~transducer~~ sensor monitors pressure at each of the plurality of ports to determine if a bladder is connected thereto and sends a representative signal to the controller.

6. (Original) A compression treatment system as recited in claim 2, wherein the controller includes separate valves that regulate inflation of the bladders.

7. (Cancelled) ~~A compression treatment system as recited in claim 6, further defining a pneumatic circuit, wherein the pressure sensor transducer is coupled to the pneumatic circuit and disposed between the pressurized fluid source and the valves in the pneumatic circuit.~~

8. (Currently Amended) A compression treatment system as recited in claim 1 ~~7~~, wherein the pressure sensor ~~transducer~~ is configured to monitor pressure of each of the bladders.

9. (Currently Amended) A compression treatment system as recited in claim 1, further comprising a foot bladder communicating with the pressure sensor ~~transducer~~.

10. (Currently Amended) A compression treatment system comprising:

a first bladder supported about a limb;

a second bladder supported about the limb, the first and second bladders being in fluid communication with a fluid source and the first and second bladders being inflated such that the first bladder is inflated for a first time period and the second bladder is inflated for a second time period, the second time period being initiated within the first time period;

a third bladder supported about a foot, the third bladder being in fluid communication with the fluid source; and

a pneumatic control circuit located at a controller housed separately from the inflatable bladders, the pneumatic control circuit including the controller, a single pressure sensor, a single check valve, the fluid source and a plurality of solenoid valves,

~~a~~ the single pressure sensor, located between the fluid source and solenoid valves, communicating with the bladders and the ~~a~~ check valve operably connected to the fluid source and located between the fluid source and solenoid valves, wherein the single check valve prevents ~~for preventing fluid~~ leakage out of a measuring bladder, the single pressure sensor measures ~~back through a pump for monitoring~~ bladder pressure ~~during~~ in cooperation with the controller to calculate venous refill time at the measured bladder ~~detection~~.

11. (Original) A compression treatment system as recited in claim 1, wherein the pressurized fluid source alternately inflates the bladders disposed about the limb and the bladder disposed about the foot.

12. (Original) A compression treatment system as recited in claim 10, further comprising a controller that communicates

with the pressurized fluid source and the pressure transducer, the controller being configured to monitor and regulate pressure in the bladders.

13. (Original) A compression treatment system as recited in claim 11, wherein the controller is disposed with a housing that is portable.

14. (Original) A compression treatment system as recited in claim 11, wherein the controller includes separate valves that regulate inflation of the bladders.

15. (Cancelled) ~~A compression treatment system as recited in claim 14, further defining a pneumatic circuit, wherein the pressure transducer is coupled to the pneumatic circuit and disposed between the pressurized fluid source and the valves in the pneumatic circuit.~~

16. (Original) A compression treatment system as recited in claim 10, wherein the pressure transducer is configured to monitor pressure of each of the bladders.

17. (Amended) A compression treatment system comprising:

a first plurality of bladders supported about a first limb;

a second plurality of bladders supported about a second limb, the bladders being in fluid communication with a fluid source and the bladders being inflated such that:

a first bladder of the first plurality of bladders is inflated for a first time period and a second bladder of the first plurality of bladders is inflated for a second time period, the second time period being initiated within the first time period, and

a first bladder of the second plurality of bladders is inflated for a third time period and a second bladder of the second plurality of bladders is inflated for a fourth time period, the fourth time period being initiated within the third time period; and

a pneumatic control circuit located at a controller housed separately from the inflatable bladders, the pneumatic control circuit including the controller, a single pressure sensor, a single check valve, the fluid source and a plurality of solenoid valves,

~~a~~ the single pressure sensor, located between the fluid source and solenoid valves, communicating with the bladders and the ~~a~~ check valve operably connected to the fluid source and located between the fluid source and solenoid valves, wherein

the single check valve prevents ~~for preventing fluid~~ leakage out of a measuring bladder, the single pressure sensor measures ~~back through a pump for monitoring~~ bladder pressure ~~during~~ in cooperation with the controller to calculate venous refill time at the measured bladder ~~detection~~.

18. (Original) A compression treatment system as recited in claim 17, further comprising a controller that is disposed with a housing that is portable, the controller communicating with the pressurized fluid source and the pressure transducer, the controller being configured to monitor and regulate pressure in the bladders.

19. (Original) A compression treatment system as recited in claim 1, wherein the pressurized fluid source alternately inflates the bladders disposed about the first limb and the bladders disposed about the second limb.

20. (Currently Amended) A compression treatment system comprising:

a first plurality of bladders being supported about a first limb and a second plurality of bladders being supported about a second limb;

each bladder of the first plurality of bladders and the second plurality of bladders having a separate valve in

communication therewith, the valves being in fluid communication with a fluid source and the bladders being inflated such that:

a first valve is open such that a first bladder of the first plurality of bladders is inflated for a first time period and a second valve is open such that a second bladder of the first plurality of bladders is inflated for a second time period, the second time period being initiated within the first time period, and a third valve is open such that a third bladder of the first plurality is inflated for a third time period, the third time period being initiated within the second time period, and

a fourth valve is open such that a first bladder of the second plurality of bladders is inflated for a fourth time period and a fifth valve is open such that a second bladder of the second plurality of bladders is inflated for a fifth time period, the fifth time period being initiated within the fourth time period, and a sixth valve is open such that a sixth bladder of the second plurality is inflated for a sixth time period, the sixth time period being initiated within the fifth time period;

a pneumatic control circuit located at a controller housed separately from the inflatable bladders, the pneumatic control circuit including the controller, a single pressure sensor, a

single check valve, the fluid source and a plurality of solenoid valves,

the ~~a~~ controller ~~that~~ communicates with the pressurized fluid source and the pressure transducer, the controller being configured to monitor and regulate pressure in the bladders~~.~~,

~~a~~ the single pressure sensor, located between the fluid source and solenoid valves, communicating with the bladders and the ~~a~~ check valve operably connected to the fluid source and located between the fluid source and solenoid valves, wherein the single check valve prevents ~~for preventing fluid~~ leakage out of a measuring bladder, the single pressure sensor measures ~~back through a pump for monitoring~~ bladder pressure ~~during~~ in cooperation with the controller to calculate venous refill time at the measured bladder ~~detection~~.

21. (Cancelled)

22. (Cancelled)

23. (Cancelled)

24. (Cancelled)

25. (Cancelled)

26. (Previously Presented) A compression treatment system as recited in claim 1, wherein the check valve operates without an electrical signal to a controller.

27. (Previously Presented) A compression treatment system as recited in claim 10, wherein the check valve operates without an electrical signal to a controller.

28. (Previously Presented) A compression treatment system as recited in claim 17, wherein the check valve operates without an electrical signal to a controller.

29. (Previously Presented) A compression treatment system as recited in claim 20, wherein the check valve operates without an electrical signal to a controller.

30. (Previously Presented) A compression treatment system as recited in claim 21, wherein the check valve operates without an electrical signal to a controller.

31. (Previously Presented) A compression treatment system as recited in claim 25, wherein the check valve operates without an electrical signal to a controller.

32. (New) A compression treatment system as recited in claim 17, wherein the measured bladder is selected from a group

comprising the first bladder, second bladder, third bladder, and fourth bladder.